

## IN THE CLAIMS

The following is a listing of the claims in the application with claim 3 shown as amended.

### LISTING OF CLAIMS:

**2. (Currently Amended)** The connector equipped with a valve as described in claim 3, further comprising a valve cap receiving a second axial-side end of said compression spring and being integrally formed with a first axial-side end of said cylindrical bushing.

**3. (Currently Amended)** A connector equipped with a valve, comprising:

a connector housing comprising:

a through path;

a tube connection section being formed at a first axial side;

a pipe insertion section being formed at a second axial side;

a valve housing section disposed between a pipe insertion section side end of said tube connection section and said pipe insertion section;

an inner diameter of said valve housing section being larger than an inner diameter of said tube connection section;

an internal valve disposed in said connector housing to open and close said through path and comprising:

a valve seat surface formed on an inner surface of said housing between said tube connection section and said valve housing section;

~~—a closing section having an outer perimeter section;~~

~~—an abutting surface formed on said outer perimeter section and abutting said valve seat surface;~~

a main valve body housed in said valve housing section and allowing axial movement, the main valve body including a closing section having an outer perimeter section and an abutting surface formed on said outer perimeter section and abutting said valve seat surface;

a compression spring biasing said main valve body toward a first axial side;

a cylindrical bushing being fitted to said pipe insertion section and filling a space between an inner perimeter surface of a first axial side of said pipe insertion section and an insertion-side end of an inserted pipe body;

a housing-side guide extending from said closing section to a second axial side and sliding over an inner perimeter surface of said valve housing section; and

a connection-side guide extending toward a first axial side from said closing section and sliding over an inner perimeter surface of said tube connection section.

**4. (Original)** The connector equipped with a valve as described in claim 3,  
further comprising;

a support groove formed on a second axial side of said housing-side guide of said main valve body wherein a first axial-side end of said compression spring is held and supported in said support groove.

**5. (Currently Amended)** The connector equipped with a valve as described in claim 3, further comprising a small through-hole communicating with said through-path at both axial sides of said closing section and formed in said closing section of said main valve body.

**6. (Currently Amended)** The connector equipped with a valve as described in claim 3, wherein said valve seat surface is formed with a linear cross-section shape and said abutting surface of said closing section is formed as an arc projecting outward in cross section.